



Hardwood Floor Refresher



DESCRIPTION:

Bona® Swedish Formula® Hardwood Floor Refresher is a specially formulated waterborne urethane maintenance coating for all unwaxed, polyurethane finished floors that are dull, scratched, or show signs of wear. Refresher restores the beauty of wood floors, making old floors look new.

FEATURES:

- Refreshes appearance of unwaxed wood floors
- Dries in one hour
- Restores gloss
- Non-toxic, waterbased formula – The Environmental Choice®
- Recoatable with finish
- Easy to use

RECOMMENDED USE:

- Residential and commercial unwaxed polyurethane finished wood floors
- Can be used on "aluminum oxide" and "ceramic" type UV finishes.



DIRECTIONS FOR USE:

Provides a crystal clear, highly durable gloss shine to polyurethane finished wood floors that are dull, worn, scratched or show signs of wear. It refreshes the appearance of these floors with a new bright luster. Use up to 4 times per year if necessary to restore gloss and shine. **NOTE: THE APPLICATION OF REFRESHER TO SATIN OR LOW GLOSS SHEENS WILL INCREASE THE GLOSS LEVEL. ALWAYS DO A TEST SECTION FIRST. REFRESHER IS INTENDED TO MAINTAIN THE FLOOR BETWEEN PROFESSIONALLY APPLIED FINISH COATS. IT IS NOT INTENDED TO REPLACE A PROFESSIONAL FINISH APPLICATION.**

PRECAUTIONS

For regular cleaning use Bona® Swedish Formula® Hardwood Floor Cleaner and the Bona MicroPlus™ Mop. Refresher is for use on unwaxed, polyurethane finished wood floors only.

DO NOT USE OVER ANY FLOOR THAT HAS BEEN WAXED OR OILED. WAX AND OIL RESIDUES WILL PREVENT THE PROPER ADHESION OF REFRESHER TO THE FLOOR. IF YOUR FLOOR HAS BEEN PREVIOUSLY COATED WITH AN ACRYLIC-TYPE MAINTENANCE COATING, IT MUST BE THOROUGHLY REMOVED PRIOR TO USING REFRESHER. FOLLOW THE STRIPPING INSTRUCTIONS FOR THAT PRODUCT OR CONTACT THE MANUFACTURER FOR THEIR RECOMMENDATION. ALWAYS TEST FLOORS FOR ADHESION AND APPEARANCE IN AN INCONSPICUOUS AREA BEFORE USE.

REFRESHER IS NOT A CLEANER. IT IS A FINISH AND IS DESIGNED TO LEAVE A PROTECTIVE COATING ON YOUR FLOOR WHEN PROPERLY APPLIED. IT IS NON-STRIPPABLE.

KEEP OUT OF REACH OF CHILDREN. MAY CAUSE GASTROINTESTINAL IRRITATION. IF SWALLOWED, DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. KEEP FROM FREEZING. DO NOT MIX WITH ANY OTHER PRODUCTS.

NOTICE: BUYER ASSUMES ALL RESPONSIBILITY FOR PROPER USE IN ACCORDANCE WITH LABEL DIRECTIONS. RESULTS MAY VARY ACCORDING TO INDIVIDUAL APPLICATION TECHNIQUES AND PRIOR CONDITION OF FLOOR. SINCE REFRESHER IS A PERMANENT COATING, ALWAYS DO A TEST SECTION FIRST.

INITIAL APPLICATION:

NOTE: Remove all furniture, rugs and obstructions. Close all windows and doors to keep airborne dust and airflow to a minimum.

1. Vacuum, sweep or dust mop to remove loose dirt and grit from your floor. Clean floor thoroughly with Bona® Swedish Formula® Hardwood Floor Cleaner and the Bona® MicroPlus™ Mop using the MicroPlus™ blue cleaning pad. Repeat to ensure that dirt will not be trapped in the Refresher. **MAKE SURE FLOOR IS COMPLETELY DRY BEFORE APPLYING REFRESHER.**

2. Rock container back & forth several times before opening. Apply Refresher with the cream colored MicroPlus™ Refresher Applicator Pad attached to the MicroPlus Mop Base. Prepare the applicator pad by slightly dampening it with water. Apply Refresher in a 1"-2" wide wavy line on the floor. Work on a small section at a time, about 4'x6'. **DO NOT USE THE SAME PAD YOU USED FOR CLEANING TO APPLY REFRESHER. DO NOT USE STRING MOPS, COTTON MOPS OR SPONGE MOPS TO APPLY REFRESHER. USE OF CONTAMINATED APPLICATORS MAY CAUSE A CLOUDY APPEARANCE.**

3. Spread Refresher over entire small section making sure all wood is completely covered. For best results, apply an even consistent coat. **REFRESHER SHOULD BE APPLIED AT 500 SQUARE FEET PER QUART (32oz). BE SURE TO KEEP THE APPLICATOR WET WITH REFRESHER. IF REFRESHER IS SPREAD TOO THIN, STREAKING MAY OCCUR.**

4. Smooth out Refresher going with the grain of the wood. Continue the process in sections until the entire floor is coated. Allow to dry a minimum of 1 hour before walking on coated floors. If a higher gloss level is desired, a second coat may be applied after 2 hours. **ALWAYS COAT ENTIRE FLOOR TO ENSURE AN EVEN APPEARANCE AND SHEEN.**

NOTE: Avoid heavy traffic and replacement of furniture and rugs for 24 hours after final coat. Clean tools with soap and water immediately after use. Rinse applicator thoroughly.



1. Clean



2. Apply



3. Spread



4. Smooth

SPECIFICATIONS/PHYSICAL DATA:

Physical Characteristics:

Ingredients - Water, polyurethane resin, N-Methyl-2-Pyrrolidone, Dipropylene Glycol Monomethyl Ether and Dipropylene Glycol n-Butyl Ether

Color - Milky white (wet)

pH - 8.0

Stability - 1 year shelf life

Density - 8.39 lbs./gallon (1.01 S.G.)

Gloss Level - (60°) >85

VOC - Does not exceed 350 grams per liter (2.9 lbs. per gallon VOC)

Odor - Non-offending

Flash Point - > 200° F

Solids - 10%

Viscosity - (#4 Ford cup @ 25° C) 10-12 seconds

Application Characteristics:

Coverage - 500 sq. ft. per quart

Clarity - Clear when dry

Leveling - Excellent

Percent Cured After 24 Hours - 80%

Application Tools - Reusable MicroPlus™ Applicator Pad

Packaging - 1-quart plastic bottle

Drying Time - 1 hour

Defoaming - Excellent

Max. Cure - 100% after 1 week

BonaKemi USA, Inc.

14805 E. Moncrieff Place, Aurora, CO 80011-1207 • (303) 371-1411 • (800) 872-5515 • FAX (303) 371-6958 • www.bonakemi.com
Item #3025 © 11/04 BonaKemi USA, Inc.