

# Bamboo

A hardy Asian tradition finds new life as an exotic alternative to hardwood.

## CONSTRUCTION:

**Solid:** Consists of solid bamboo strips, laminated together in a vertical or horizontal direction, then milled into individual boards.

**Crosshatch:** Three-layer all-bamboo engineered construction with transverse middle layer for added strength and stability.

## INSTALLATION OPTIONS:




Above grade – Yes  
On grade – Yes  
Below grade – No




Yes\*



Yes\*\*



No



No

\*Professional installation recommended. \*\*Professional installation required.

## BOARD SIZE:

**Solid:** Width: 3¾” (96mm) Thickness: 5/8” (15mm)

Length: Approx. 73” (1860mm)

**Crosshatch:** Width: 6” (154mm) Thickness: 5/8” (15mm)

Length: Approx. 73” (1850mm)

## PKG CONTENTS:

**Solid:** 19.22 sq/ft (1.785 sq/m)

**Crosshatch:** 18.4 sq/ft (1.709 sq/m)

(Add 5% cutting allowance when calculating amount of flooring required.)


**FACTORY FINISH:** Polyurethane with aluminum oxide

**GLOSS LEVEL:** 25% (+/- 5%)


**WARRANTY:** 25 year residential wear warranty on finish

**Your KENTWOOD™ dealer:**

## COLORS & SPECIES




**Horizontal Natural**



**Horizontal Carbonized**



**Vertical Natural**



**Vertical Carbonized**